

  
**SAFETY DATA SHEET**  
**SUPERWAX**

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

Product name SUPERWAX

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Uses advised against No specific uses advised against are identified.

**1.3. Details of the supplier of the safety data sheet**

Supplier Chemisure  
Heathcote Industrial Estate,  
Warwick,  
CV34 6TJ  
01926 887988

**1.4. Emergency telephone number**

Emergency telephone +44 (0) 1926 887988 (Mon-Fri 9:00am-5:00pm GMT)

National emergency telephone number +44 (0)870 600 6266 [UK National Poisons Control Information Service (NPIS) Center]

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification (EC 1272/2008)**

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319

Environmental hazards Not Classified

**2.2. Label elements**

**Pictogram**



Signal word Warning

Hazard statements H315 Causes skin irritation.  
H319 Causes serious eye irritation.

Precautionary statements P264 Wash contaminated skin thoroughly after handling.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
P302+P352 IF ON SKIN: Wash with plenty of water.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P321 Specific treatment (see medical advice on this label).  
P332+P313 If skin irritation occurs: Get medical advice/ attention.  
P337+P313 If eye irritation persists: Get medical advice/ attention.  
P362+P364 Take off contaminated clothing and wash it before reuse.

**2.3. Other hazards**

# SUPERWAX

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

<b>Distillates (petroleum), hydrotreated middle</b> <span style="float: right;"><b>1-5%</b></span>		
CAS number: 64742-46-7	EC number: 265-148-2	REACH registration number: 01-2119827000-58-XXXX
<b>Classification</b> Asp. Tox. 1 - H304	<b>Classification (67/548/EEC or 1999/45/EC)</b> Xn; R65	
<b>dicocodimethyl ammonium chloride</b> <span style="float: right;"><b>1-5%</b></span>		
CAS number: 61789-77-3	EC number: 263-087-6	REACH registration number: 01-2119486994-16-XXXX
M factor (Acute) = 1		
<b>Classification</b> Flam. Liq. 3 - H226 Acute Tox. 4 - H302 Skin Corr. 1C - H314 Eye Dam. 1 - H318 Aquatic Acute 1 - H400	<b>Classification (67/548/EEC or 1999/45/EC)</b> Xn; R22. C; R34. N; R50. R10	
<b>2-butoxyethanol</b> <span style="float: right;"><b>&lt;1%</b></span>		
CAS number: 111-76-2	EC number: 203-905-0	REACH registration number: 01-2119475108-36-XXXX
<b>Classification</b> Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319		
<b>propan-2-ol</b> <span style="float: right;"><b>&lt;1%</b></span>		
CAS number: 67-63-0	EC number: 200-661-7	REACH registration number: 01-2119457558-25-XXXX
<b>Classification</b> Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>General information</b>	If in doubt, get medical attention promptly.
<b>Inhalation</b>	Get medical attention if any discomfort continues.
<b>Ingestion</b>	Give plenty of water to drink. Move affected person to fresh air at once. Get medical attention if any discomfort continues.

# SUPERWAX

<b>Skin contact</b>	Remove contaminated clothing immediately and wash skin with soap and water. Rinse with water.
<b>Eye contact</b>	Get medical attention if any discomfort continues. Remove affected person from source of contamination. Rinse with water. Remove contact lenses, if present and easy to do. Continue rinsing. Continue to rinse for at least 10 minutes.
<b>Protection of first aiders</b>	First aid personnel should wear appropriate protective equipment during any rescue.

## **4.2. Most important symptoms and effects, both acute and delayed**

<b>General information</b>	Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.
<b>Inhalation</b>	May cause discomfort. May be harmful if inhaled.
<b>Ingestion</b>	A single exposure may cause the following adverse effects: Nausea, vomiting. May be harmful if swallowed.
<b>Skin contact</b>	May be harmful in contact with skin. May cause discomfort. Prolonged and frequent contact may cause redness and irritation.
<b>Eye contact</b>	May be slightly irritating to skin and eyes. Prolonged or repeated exposure may cause severe irritation.

## **4.3. Indication of any immediate medical attention and special treatment needed**

<b>Notes for the doctor</b>	Treat symptomatically.
<b>Specific treatments</b>	Not applicable.

## **SECTION 5: Firefighting measures**

### **5.1. Extinguishing media**

<b>Suitable extinguishing media</b>	The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.
<b>Unsuitable extinguishing media</b>	Not applicable.

### **5.2. Special hazards arising from the substance or mixture**

<b>Specific hazards</b>	The product is non-combustible. None known.
<b>Hazardous combustion products</b>	None known.

### **5.3. Advice for firefighters**

<b>Protective actions during firefighting</b>	Avoid breathing fire gases or vapours.
<b>Special protective equipment for firefighters</b>	Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

<b>Personal precautions</b>	Avoid contact with eyes and prolonged skin contact.
-----------------------------	---

### **6.2. Environmental precautions**

<b>Environmental precautions</b>	No negative effects on the aquatic environment are known. Not regarded as dangerous for the environment.
----------------------------------	--

### **6.3. Methods and material for containment and cleaning up**

<b>Methods for cleaning up</b>	Contain spillage with sand, earth or other suitable non-combustible material. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
--------------------------------	---

# SUPERWAX

## 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. For waste disposal, see Section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Avoid contact with skin, eyes and clothing. Avoid contact with eyes and prolonged skin contact.

**Advice on general occupational hygiene** Clean equipment and the work area every day. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Keep only in the original container. Keep container tightly closed in a cool place.

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### 2-butoxyethanol

Long-term exposure limit (8-hour TWA): WEL 25 ppm 123 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 50 ppm 246 mg/m<sup>3</sup>

Sk

##### propan-2-ol

EH40 WEL, Time Weighted Average (TWA): 400ppm, 999mg/m<sup>3</sup>

EH40 WEL, Short Term Exposure Limit (STEL): 500ppm, 1250 mg/m<sup>3</sup>

ELV (IE), Short Term Exposure Limit (STEL): 400 ppm

ELV (IE), Time Weighted Average (TWA): 200 ppm

Sk = Can be absorbed through the skin.

#### 2-butoxyethanol (CAS: 111-76-2)

<b>Ingredient comments</b>	WEL = Workplace Exposure Limit
<b>DNEL</b>	Industry - Dermal; Short term systemic effects: 89 mg/kg/day Industry - Inhalation; Short term systemic effects: 1091 mg/m <sup>3</sup> Industry - Inhalation; Short term local effects: 246 mg/m <sup>3</sup> Industry - Dermal; Long term systemic effects: 125 mg/kg/day Industry - Inhalation; Long term systemic effects: 98 mg/m <sup>3</sup> Consumer - Inhalation; Short term systemic effects: 426 mg/m <sup>3</sup> Consumer - Oral; Short term systemic effects: 26.7 mg/kg/day Consumer - Dermal; Short term systemic effects: 89 mg/kg/day Consumer - Dermal; Long term systemic effects: 75 mg/kg/day Consumer - Inhalation; Long term local effects: 147 mg/m <sup>3</sup> Consumer - Inhalation; Long term systemic effects: 59 mg/m <sup>3</sup> Consumer - Oral; Long term systemic effects: 6.3 mg/kg/day

# SUPERWAX

<b>PNEC</b>	Fresh water; 8.8 mg/l Marine water; 0.88 mg/l Sediment (Freshwater); 8.14 mg/kg Sediment (Marinewater); 3.46 mg/kg Soil; 2.8 mg/kg STP; 463 mg/l
-------------	---

## propan-2-ol (CAS: 67-63-0)

<b>DNEL</b>	Workers - Dermal; Long term systemic effects: 888 mg/kg/day Workers - Inhalation; Long term systemic effects: 500 mg/m <sup>3</sup> Consumer - Dermal; Long term systemic effects: 319 mg/kg/day Consumer - Inhalation; Long term systemic effects: 89 mg/m <sup>3</sup> Consumer - Oral; Long term systemic effects: 26 mg/kg/day
-------------	--

<b>PNEC</b>	- Fresh water; 140.9 mg/l - Marine water; 140.9 mg/l - Intermittent release; 140.9 mg/l - STP; 2251 mg/l - Sediment; 552 mg/kg - Soil; 28 mg/kg
-------------	--

## 8.2. Exposure controls

### Protective equipment



### Appropriate engineering controls

Avoid inhalation of vapours and spray/mists. Observe any occupational exposure limits for the product or ingredients.

### Eye/face protection

Contact lenses should not be worn when working with this chemical. Chemical splash goggles.

### Hand protection

Wear protective gloves. To protect hands from chemicals, gloves should comply with European Standard EN374.

### Other skin and body protection

Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.

### Hygiene measures

Good personal hygiene procedures should be implemented. Do not eat, drink or smoke when using this product. Eye wash facilities and emergency shower must be available when handling this product. Wash promptly with soap and water if skin becomes contaminated. Wash contaminated clothing before reuse.

### Respiratory protection

Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible.

### Environmental exposure controls

Keep container tightly sealed when not in use.

## SECTION 9: Physical and Chemical Properties

### 9.1. Information on basic physical and chemical properties

### 9.2. Other information

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

#### Reactivity

There are no known reactivity hazards associated with this product.

### 10.2. Chemical stability

# SUPERWAX

**Stability** Stable at normal ambient temperatures and when used as recommended.

## 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** None known.

## 10.4. Conditions to avoid

**Conditions to avoid** Avoid exposure to high temperatures or direct sunlight. Avoid freezing.

## 10.5. Incompatible materials

**Materials to avoid** Strong oxidising agents. Strong reducing agents.

## 10.6. Hazardous decomposition products

**Hazardous decomposition products** May emit toxic fumes under fire conditions.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity - oral

**ATE oral (mg/kg)** 31,746.03

**Inhalation** Vapours may irritate throat/respiratory system. May be harmful if inhaled.

**Ingestion** May cause discomfort if swallowed. May be harmful if swallowed.

**Skin contact** Prolonged skin contact may cause redness and irritation. May be harmful in contact with skin.

**Eye contact** May cause irritation. May cause serious eye damage.

## SECTION 12: Ecological Information

**Ecotoxicity** The product is not expected to be hazardous to the environment.

### 12.1. Toxicity

### 12.2. Persistence and degradability

### 12.3. Bioaccumulative potential

### 12.4. Mobility in soil

**Mobility** The product is soluble in water.

### 12.5. Results of PBT and vPvB assessment

### 12.6. Other adverse effects

**Other adverse effects** None known.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**General information** Dispose of waste product or used containers in accordance with local regulations

## SECTION 14: Transport information

### 14.1. UN number

### 14.2. UN proper shipping name

### 14.3. Transport hazard class(es)

### 14.4. Packing group

### 14.5. Environmental hazards

### 14.6. Special precautions for user

# SUPERWAX

## 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

<b>EU legislation</b>	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
-----------------------	--

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

### SECTION 16: Other information

<b>General information</b>	Only trained personnel should use this material.
<b>Issued by</b>	HS&E Manager.
<b>SDS number</b>	7771
<b>Hazard statements in full</b>	H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H336 May cause drowsiness or dizziness. H400 Very toxic to aquatic life.

**Code**

**Other Information**

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.